

## PD-Series LED-backlit Display 55" | 49" | 42"

### The Right Building Blocks for Your Video Wall



Built for digital signage, the PD-Series features a 6.5mm narrow bezel and a full slate of inputs including HDMI with HDCP, DisplayPort 1.2 for 4K 2x2 video wall setups, and RS-232 and RJ45 ports for remote and network-based control. The displays also include other signage-friendly features such as landscape and portrait modes, scheduling capabilities, and a switch-on delay mechanism for use in video walls. Furthermore, the PD-Series also fits for security control room usages with its premium-grade panel and 24/7 design.






### High Visibility

The PD-Series offers pristine images that maximize visibility, making videos shown on the display stand out in any setting. The 700 nits high brightness, 10 bit color depth, and 5 ms response time ensure life-like visuals, all complemented by a 178-degree viewing angle that allows the display to be seen by all.

### Ideal for Video Walls

The PD-Series is an excellent choice for video walls with a variety of features, which make installation and setup convenient including DisplayPort 1.2 support for easy 4K 2x2 video wall setup, a switch-on delay mechanism, a logo-free design, and a premium-grade panel for 24/7 operation.




### Simple Content Scheduling

The embedded USB media player allows users to conveniently play content from a USB drive. Simply create scheduled playlists and configure playback settings with the included remote control to display your personalized content.

### Easy Control for Large-Scale Digital Signage

Its built-in scheduler and OPS slot are complemented by IR / RS-232 looping and Ethernet control capabilities to easily control, setup and maintain large-scale digital signage video walls installations.



### Features

- LED-backlit technology with 1920 x 1080 Full HD resolution
- 6.5mm narrow bezel, 57mm slim depth design for digital signage applications
- Tiling function for easy video wall setup (supports up to 10 x 10)
- Versatile connectivity: DisplayPort in/out, HDMI in/out, DVI in/out, VGA in/out, Composite/Component
- RJ45, RS-232 in/out and IR in/out allow network-based and remote control
- Scheduled-based content playback based on time and day
- DLNA support to access media files over a network

- USB media playback
- OPS slot for easy digital signage player integration
- Premium-grade panel for high reliability and long product lifetime
- Anti-Burn-in™ technology
- Designed for 24/7 operation
- HeatControl sensors automatically activate the internal cooling fans
- Durable metal housing design



## Specifications

### PD-55

### PD-49

### PD-42

Specifications		PD-55	PD-49	PD-42
<b>Panel</b>	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Viewing Angle (H/V) Disply Colour Response Time	LED-Backlit TFT LCD 54.6" FHD 1920 x 1080 0.63 mm 700 cd/m <sup>2</sup> 1300:1 178°/178° 1.07 B 5 ms	LED-Backlit TFT LCD 48.5" FHD 1920 x 1080 0.5593 mm 700 cd/m <sup>2</sup> 1300:1 178°/178° 1.07 B 5 ms	LED-Backlit TFT LCD 41.9" FHD 1920 x 1080 0.4833 mm 700 cd/m <sup>2</sup> 1300:1 178°/178° 1.07 B 5 ms
<b>Frequency (H/V)</b>	H Freq. V Freq.	31 kHz - 92 kHz 48 Hz - 85 Hz	31 kHz - 92 kHz 48 Hz - 85 Hz	31 kHz - 92 kHz 48 Hz - 85 Hz
<b>Input</b>	VGA DVI HDMI DisplayPort Composite Component (YPbPr) USB	15-Pin D-sub x 1 24-Pin DVI-D x 1 HDMI 1.3b x 2 DisplayPort 1.2 x 1 BNC x 1 BNC x 1 USB 2.0 x 1 (Service Port / Media Playback)	15-Pin D-sub x 1 24-Pin DVI-D x 1 HDMI 1.3b x 2 DisplayPort 1.2 x 1 BNC x 1 BNC x 1 USB 2.0 x 1 (Service Port / Media Playback)	15-Pin D-sub x 1 24-Pin DVI-D x 1 HDMI 1.3b x 2 DisplayPort 1.2 x 1 BNC x 1 BNC x 1 USB 2.0 x 1 (Service Port / Media Playback)
<b>Output</b>	VGA/ DVI/ HDMI DisplayPort	29-Pin DVI-I x 1 DisplayPort 1.2 x 1	29-Pin DVI-I x 1 DisplayPort 1.2 x 1	29-Pin DVI-I x 1 DisplayPort 1.2 x 1
<b>External Control</b>	RS-232 in/out IR in/out RJ45	2.5 mm phone jack x 2 3.5 mm phone jack x 2 RJ45	2.5 mm phone jack x 2 3.5 mm phone jack x 2 RJ45	2.5 mm phone jack x 2 3.5 mm phone jack x 2 RJ45
<b>Audio</b>	Audio In  Audio Out Internal Speaker External Speaker	Stereo audio jack for PC (3.5 mm) x 1 Stereo audio for video (RCA) x 1 Stereo audio jack (3.5 mm) x 1 10 W x 2 Jack with push button to switch internal / external	Stereo audio jack for PC (3.5 mm) x 1 Stereo audio for video (RCA) x 1 Stereo audio jack (3.5 mm) x 1 10 W x 2 Jack with push button to switch internal / external	Stereo audio jack for PC (3.5 mm) x 1 Stereo audio for video (RCA) x 1 Stereo audio jack (3.5 mm) x 1 10 W x 2 Jack with push button to switch internal / external
<b>Other Connectivity</b>	OPS Slot	Yes	Yes	Yes
<b>Power</b>	Power Supply Power Requirement Consumption Stand By	Internal AC 110-240 V < 148 W (On) < 0.5 W (Stand-by/Off)	Internal AC 110-240 V < 131 W (On) < 0.5 W (Stand-by/Off)	Internal AC 110-240 V < 118 W (On) < 0.5 W (Stand-by/Off)
<b>Operating Conditions</b>	Temperature Humidity	0°C ~ 40°C (32°F ~ 104°F) 20%-80% (No condensation)	0°C ~ 40°C (32°F ~ 104°F) 20%-80% (No condensation)	0°C ~ 40°C (32°F ~ 104°F) 20%-80% (No condensation)
<b>Storage Conditions</b>	Temperature Humidity	-20°C ~ 60°C (-4°F ~ 140°F) 5%-90% (No condensation)	-20°C ~ 60°C (-4°F ~ 140°F) 5%-90% (No condensation)	-20°C ~ 60°C (-4°F ~ 140°F) 5%-90% (No condensation)
<b>Mounting</b>	VESA FPMPMI	Yes (400 x 400 mm)	Yes (400 x 400 mm)	Yes (200 x 200 mm)
<b>Dimensions</b>	Product with handle (W x H x D) Packaging (W x H x D)	1228.6 x 699.4 x 71.1 mm (48.4" x 27.5" x 2.8") 1444.0 x 922.0 x 223.0 mm (56.9" x 36.3" x 8.8")	1092.3 x 622.5 x 71.1 mm (43.0" x 24.5" x 2.8") 1308.0 x 846.0 x 203.0 mm (51.5" x 33.3" x 8.0")	946.9 x 541.0 x 71.1 mm (37.3" x 21.3" x 2.8") 1123.0 x 743.0 x 203.0 mm (44.2" x 29.3" x 8.0")
<b>Weight</b>	w/o base Packaging	24.7 kg (54.5 lb) 31.2 kg (68.8 lb)	19.0 kg (41.9 lb) 24.9 kg (54.9 lb)	15.3 kg (33.7 lb) 19.6 kg (43.2 lb)
<b>Regulation Approval</b>	Certification & Compliance	CE, REACH, WEEE, RoHS, CB, FCC	CE, REACH, WEEE, RoHS, CB	CE, REACH, WEEE, RoHS, CB, FCC, BSMI
<b>Accessories</b>	Supplied	Quick Start Guide, Power Cord, RS-232 Cable, VGA Cable, Daisy Chain Cable, Remote Control	Quick Start Guide, Power Cord, RS-232 Cable, VGA Cable, Daisy Chain Cable, Remote Control	Quick Start Guide, Power Cord, RS-232 Cable, VGA Cable, Daisy Chain Cable, Remote Control
<b>Optional Accessories</b>		Ceiling Mount: CMP-01+LMK-01 (Landscape only) Wall Mount: LMK-01, LMK-03 Wall Mount Arm: LMA-01 Stand Base: STD-04	Ceiling Mount: CMP-01+LMK-01 (Landscape only) Wall Mount: LMK-01, LMK-03 Wall Mount Arm: LMA-01 Stand Base: STD-04	Ceiling Mount: CMP-01+LMK-02 Wall Mount: LMK-01, LMK-02, WMK-03, WMA-01 Wall Mount Arm: LMA-01 Stand Base: STD-04

**Global Headquarters**

Taipei, Taiwan

**EMEA Regional Headquarters**

Capelle a/d IJssel, The Netherlands

**North & South America Regional Headquarters**

San Jose, CA, U.S.A.

**Asia-Pacific Regional Headquarters**

Taipei, Taiwan

**Canada Sales Office**

Vancouver, B.C., Canada

**China Sales Office**

Shanghai, China

**Czech Republic Sales Office**

Brno, Czech Republic

**Denmark Sales Office**

Støvring, Denmark

**Germany Sales Office**

Mechernich, Germany

**Italy Sales Office**

Livorno, Italy

**Poland Sales Office**

Warsaw, Poland

**Spain Sales Office**

Barcelona, Spain

**Ukraine Sales Office**

Lviv, Ukraine

[www.agneovo.com](http://www.agneovo.com)