



# SMT-3215

32 inch LED monitor



## Key Features

- 32 inch FHD Monitor, support up to 1920×1080 @60Hz
- Brightness 300 cd/m<sup>2</sup> (Typical), Contrast 3200:1 (Minimum) 4000:1 (Typical)
- Viewing Angle (H/V) : 178°/178°, Response Time : 20ms (Typical)
- Video Input : HDMI, DP, VGA
- Panel Life : 30,000 hours
- Designed and tested on 24/7 operation

# SMT-3215

32 inch LED monitor



## Specifications

| Display             |  |   |
|---------------------|--|---|
| Type                | LED Monitor  |   |
| Screen Size         | 31.5"  |   |
| Max. Resolution     | 1920*1080 60Hz (FHD)   |   |
| Brightness          | 300 cd/m <sup>2</sup> (Typ)  |   |
| Contrast Ratio      | 3200:1 (Min) 4000:1 (Typ)  |   |
| Aspect Ratio        | 16:9   |   |
| Viewing Angle (H/V) | 178°/178°  |   |
| Display Color       | 16.7M  |   |
| Response Time       | 20ms(Typ)  |   |
| Panel Life          | 30,000 hours   |   |
| Interface           |  |   |
| Video               | Connectors   | VGA (1) HDMI 1.4(1), DP 1.2(1) Audio-in(1) Audio-out (1)  |
| VGA                 | Connector  | 1port Analog D-sub(15 pin)  |
|                     | Available Format   | 640 x 480@60Hz, 800 x 600@56Hz/60Hz/72Hz/75Hz, 1024 x 768@60Hz/70Hz/75Hz, 1280 x 1024@60Hz/75Hz, 1440 x 900@60Hz, 1680 x 1050@60Hz, 1920 x 1080@50Hz/60Hz, 1280 x 800@60Hz, 1280 x 960@60Hz, 1280 x 720@60Hz  |
| HDMI                | Connector  | HDMI  |
|                     | Available Format   | 640 x 480@60Hz, 800 x 600@56Hz/60Hz/72Hz/75Hz, 1024 x 768@60Hz/70Hz/75Hz, 1280 x 1024@60Hz/75Hz, 1440 x 900@60Hz, 1680 x 1050@60Hz, 1920 x 1080@50Hz/60Hz, 720 x 480P60Hz, 1280 x 720P@50Hz, 720 x 576P@50Hz, 1920x1080P@50/60Hz, 1280 x 800@60Hz, 1280 x 960@60Hz, 1280 x 720@60Hz |
| DP                  | Connector  | DP  |
|                     | Available Format   | 640 x 480@60Hz, 800 x 600@56Hz/60Hz/72Hz/75Hz, 1024 x 768@60Hz/70Hz/75Hz, 1280 x 1024@60Hz/75Hz, 1440 x 900@60Hz, 1680 x 1050@60Hz, 1920 x 1080@50Hz/60Hz, 720 x 480P60Hz, 1280 x 720P@50Hz, 720 x 576P@50Hz, 1920x1080P@50/60Hz, 1280 x 800@60Hz, 1280 x 960@60Hz, 1280 x 720@60Hz |
| Audio               | Connector  | Audio in/out  |
|                     | Output Signal  | Loop-through line level(PC only), Speakers : 4Ω 2.5Wx 2   |
| On Screen Display   |  |   |
| Functions           | VESA™ DPM Compatible   |   |
| Language            | Korean, English, Русский, Deutsch, Français, Español, Italiano, Português, Chinese (Simplified), Chinese (Traditional), Japanese, Arabic |   |
| General             |  |   |

Design and specifications are subject to change without notice. The latest product information / specification can be found at [HanwhaVision.com](http://HanwhaVision.com)

Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

|               |                                  |  |
|---------------|----------------------------------|--|
| Electrical    | Input Voltage                    | AC 100 ~ 240V(50/60Hz)                   |
|               | Power Consumption                | <60W                                     |
| Environmental | Operating Temperature            | 0 ~ +40°C (+32°F ~ +104°F)               |
|               | Operating Humidity               | 10% ~ 80% (non-condensing)               |
| Mechanical    | Dimensions with Stand (WxHxD)    | 714.0*484.2*200.8mm                      |
|               | Dimensions without Stand (WxHxD) | 714.0*423.7*53.7mm                       |
|               | Weight                           | 7.28kg(with stand), 5.9Kg(without stand) |
|               | Cabinet Color                    | Black                                    |
|               | VESA Mounts Interface            | 100 x 100mm                              |