

HWD-5100M SERIES TURBO HD DVR



Key Features

Video Input and Transmission

- Connectable to Turbo HD/HDCVI/AHD/CVBS signal input
- Up to 2-ch 960p IP cameras input
- Long distance transmission over UTP and coaxial cable

Compression and Recording

- One-key enable H.264+ compression to improve encoding efficiency by up to 50% and reduce data storage costs
- Supports 1080p lite and when enabled, the image effect is similar with 1080p

Video Output

- Simultaneous HDMI/VGA output at up to 1920 × 1080 resolution

Storage and Playback

- One SATA interface (up to 6 TB capacity per HDD)
- 4/8/16-ch synchronous playback
- Smart search for efficient playback

Smart Function


- VQD (Video Quality Diagnostics)
- Unlock pattern for device login for the *admin* and clear-text password available
- GUID file can be exported for password resetting and imported for finding the forgotten password
- Supports PTZ control via Omnicast VMS of Genetec protocol

Network & Ethernet Access

- Hik-Connect & DDNS (Dynamic Domain Name System) for easy network management
- One self-adaptive 10/100Mbps network interface
- Output bandwidth limit configurable



Dimensions



 **NOTE**

The rear panel of HWD-5104/5108M provides 4/8 video input interfaces.

| Index | Description | Index | Description |
|-------|--------------------------|-------|-----------------------|
| 1 | VIDEO IN | 6 | LAN Network Interface |
| 2 | HDMI Interface | 7 | USB Interfaces |
| 3 | VGA Interface | 8 | GND |
| 4 | AUDIO OUT, RCA Connector | 9 | 12 VDC Power Input |
| 5 | AUDIO IN, RCA Connector | | |

Specifications

| Model | | HWD-5104M | HWD-5108M | HWD-5116M |
|---------------------------------|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| Video/Audio input | Video compression | H.264+/H.264 | | |
| | Analog video input | 4-ch | 8-ch | 16-ch |
| | | BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection | | |
| | Turbo HD input | 1080p25, 1080p30, 720p25, 720p30 | | |
| | AHD input | 1080p25, 1080p30, 720p25, 720p30 | | |
| | HDCVI input | 1080p25, 1080p30, 720p25, 720p30 | | |
| | CVBS input | Support | | |
| | IP video input | 1-ch | 2-ch | |
| | | Up to 960p resolution | | |
| | Audio compression | G.711u | | |
| Audio input/Two-way audio input | 1-ch, RCA (2.0 Vp-p, 1 KΩ) | | | |
| Video/Audio output | HDMI/VGA output | 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz | | |
| | Encoding resolution | When 1080p lite mode not enabled: 720p/WD1/4CIF/VGA/CIF When 1080p lite mode enabled: 1080p lite/HD 720p lite/WD1/4CIF/VGA/CIF | | |
| | Frame rate | Main stream: When 1080p lite mode enabled: 1080p lite/HD 720p lite/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) When 1080p lite mode not enabled: For 720p stream access: 720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) For SD stream access: WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) | Main stream: When 1080p lite mode enabled: 1080p lite/HD 720p lite/WD1/4CIF/VGA@12fps; CIF@25fps (P)/30fps (N) When 1080p lite mode not enabled: For 720p stream access: 720p/WD1/4CIF/VGA@12fps; CIF@25fps (P)/30fps (N) For SD stream access: WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) | |
| | | Sub-stream: 2CIF@6fps; CIF/QVGA/QCIF@25fps (P)/30fps (N) | Sub-stream: CIF/QVGA/QCIF@25fps (P)/30fps (N) | |
| | Video bit rate | 32 Kbps to 4 Mbps | | |
| | Audio output | 1-ch, RCA (Linear, 1 KΩ) | | |
| | Audio bit rate | 64 Kbps | | |
| | Dual stream | Support | | |
| | Stream type | Video, Video & Audio | | |
| | Synchronous playback | 4-ch | 8-ch | 16-ch |
| Network management | Remote connections | 32 | 128 | |
| | Network protocols | TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS | | |
| Hard disk | SATA | 1 SATA interface | | |
| | Capacity | Up to 6 TB capacity for each disk | | |
| External interface | Network interface | 1, RJ45 10M/100M self-adaptive Ethernet interface | | |
| | USB interface | Rear panel: 2 × USB 2.0 | | |
| General | Power supply | 12 VDC | | |
| | Consumption (without HDD) | ≤ 8 W | ≤ 12 W | ≤ 20 W |
| | Working temperature | -10 °C to +55 °C (14 °F to 131 °F) | | |
| | Working humidity | 10% to 90% | | |
| | Dimensions (W × D × H) | 260 × 222 × 45 mm (10.2 × 8.7 × 1.8 inch) | | |
| | Weight (without HDD) | ≤ 0.8 kg (1.8 lb) | | ≤ 1.2 kg (2.6 lb) |

Applicable Models

HWD-5104M, HWD-5108M, HWD-5116M

Distributed by



HIKVISION[®]
HiWatch Series

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
T +27 (10) 0351172
sale.africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com