

DDF4520HDV-DN

Hybrid HD Dome Camera, 1.3-Megapixel, 720p/30, SD (PAL/NTSC), H.264, Day/Night (ICR), Low-Light, Wide Dynamic Range (WDR), Motor-driven Varifocal Lens, P-Iris, PoE (Class 0), Vandal-resistant (IK10)



The DDF4520HDV-DN is a hybrid Wide Dynamic Range (WDR) HD network camera built into a vandal-resistant (IK10) dome enclosure.

The camera provides real-time HD video (720p/30) using the H.264 codec, currently, the most advanced standard for high-efficiency video compression, and supports resolutions up to 1.3-megapixel.

In addition to HD video over IP, the hybrid camera provides for a simultaneous analogue SD (PAL/NTSC) video output via BNC (CVBS).

The camera is characterized by its Wide Dynamic Range (WDR) and allows you to capture images with highest colour fidelity and superb detail reproduction even in scenes with a wide range of contrast and strong backlighting.

The excellent low light performance also provides for clear and low noise images even in low light conditions.

Besides a comprehensive set of automatic and manual image optimization functions and many other setting options, it features automatic Day/Night operation supported by integrated ambient light sensing and a removable IR cut filter (ICR¹⁾).

In addition, the camera is equipped with a fast (large maximum aperture) and motor-driven P-Iris megapixel varifocal lens which allows for the convenient adjustment/configuration of the focal length (zoom), focus and iris (aperture) via the web browser.

The novel P-Iris control technology, designed for a precise and automatic adjustment of the best iris position (optimum aperture), thereby realizes a significantly improved image quality²⁾ with excellent contrast, brilliant clarity and enhanced detail resolution combined with a greater depth of field, under almost all lighting conditions.

At a resolution of 720p, the Digital Image Shift function additionally provides for a subsequent digital fine alignment of the image section.

Depending on the requirements, the camera can be conventionally supplied with 12V DC or conveniently operated via Power over Ethernet (PoE Class 0, IEEE 802.3af) which allows for an easy, quick and cost-effective cabling and commissioning.

Features

- 1/3" 1.3-megapixel CMOS image sensor
- Pure Digital Signal Processing
- Hybrid HD camera – HD video over IP (Ethernet, RJ45) and analogue SD (PAL/NTSC) video output via BNC (CVBS)
- Real-time HD video (720p/30)
- Wide Dynamic Range (WDR)
- Automatic Day/Night switching using ambient light sensing and ICR¹⁾ function (switching threshold level adjustable)
- Excellent low light performance
- Motor-driven megapixel varifocal lens
- Zoom, focus and iris control conveniently adjustable via web browser
- P-Iris control for an optimum image quality and significantly enhanced depth of field²⁾
- Resolution video over IP: SD (4CIF PAL/NTSC), HD (720p, SXGA-)
- Resolution analogue video output: SD (4CIF PAL/NTSC)
- Video compression: H.264, MJPEG
- Frame rate up to 30 fps
- Automatic Exposure (AE) preset and frame rate of 50/60 fps at 720p for casino applications optional³⁾
- Simultaneous Dual- or Tri-Streaming
- Manual White Balance (MWB)
- Automatic White Balance (ATW, One-Push AWB)
- Automatic Gain Control (AGC)
- Automatic Electronic Shutter (AES)
- Comprehensive set of image optimization functions like brightness, contrast, saturation and sharpness
- Digital Noise Reduction (DNR)
- Three different exposure metering modes: average metering (light information from entire scene), centre-weighted average metering and spot metering
- Privacy Zone Masking (hiding/masking of protected areas)
- Flip function (horizontal, vertical or both)
- Digital Image Shift⁴⁾
- Motion detection⁵⁾ with selectable sensitivity
- Alarm notification via DaVid Protocol⁵⁾, e-mail and FTP image upload
- Voltage supply with 12V DC or via PoE (Class 0, IEEE 802.3af)
- Low power consumption
- 3-axis adjustment
- Two available mounting variants: in-ceiling mount (IM) or surface mount (SM)
- Compact vandal-resistant (IK10) housing
- IP67 (surface mount variant)
- ONVIF compliant
- DIN EN 50130-4 compliant

1) ICR = IR Cut Filter Removable

2) Compared to conventional DC auto iris lenses

3) Optional license DLC - Casino Preset and Frame Rate 50/60 fps at 720p (004717) required. The recording at 50/60 fps is supported by the DIS-2/M NSU.

4) Digital Image Shift = Provides digital fine alignment of the image section (only applicable at 720p, vertical alignment by 120 pixels up or down)

5) Function in preparation

DDF4520HDV-DN

Hybrid HD Dome Camera, 1.3-Megapixel, 720p/30, SD (PAL/NTSC), H.264, Day/Night (ICR), Low-Light, Wide Dynamic Range (WDR), Motor-driven Varifocal Lens, P-Iris, PoE (Class 0), Vandal-resistant (IK10)

Variants/Accessories/Licences

Variants

004493.406	DDF4520HDV-DN-IM Hybrid HD dome camera, 1.3-megapixel, 720p/30, SD (PAL/NTSC), H.264, Day/Night (ICR), Low-Light, WDR, motor-driven varifocal lens, P-Iris, PoE (Class 0), vandal-resistant (IK10), in-ceiling mount variant, F1.2–F2.3 / 3–9 mm
004494.406	DDF4520HDV-DN-SM Hybrid HD dome camera, 1.3-megapixel, 720p/30, SD (PAL/NTSC), H.264, Day/Night (ICR), Low-Light, WDR, motor-driven varifocal lens, P-Iris, PoE (Class 0), vandal-resistant (IK10), surface mount variant, F1.2–F2.3 / 3–9 mm
004493.408	DDF4520HDV-DN-IM Hybrid HD dome camera, 1.3-megapixel, 720p/30, SD (PAL/NTSC), H.264, Day/Night (ICR), Low-Light, WDR, motor-driven varifocal lens, P-Iris, PoE (Class 0), vandal-resistant (IK10), in-ceiling mount variant, F1.6–F2.6 / 10–23 mm
004494.408	DDF4520HDV-DN-SM Hybrid HD dome camera, 1.3-megapixel, 720p/30, SD (PAL/NTSC), H.264, Day/Night (ICR), Low-Light, WDR, motor-driven varifocal lens, P-Iris, PoE (Class 0), vandal-resistant (IK10), surface mount variant, F1.6–F2.6 / 10–23 mm

Accessories

001044	 Tinted Bubble For in-ceiling and surface mount variant, 4.5"
001431	 EvC-1 High-Speed Ethernet data transmission via coaxial cable
001678	 Power Supply Unit (110–240 V AC -> 12 V DC) Universal power supply, 110–240 V AC to 12 V DC, 850 mA, plug adapter EU/UK/US/AUS
004316	 PoE Midspan 30 W Midspan power supply unit, 1× Ethernet port, 10/100/1000Base-T, 802.3at, 802.3af, 30 W
005017	 Wall Mount Bracket (SM Housing) Wall mount bracket with seals and internal cable routing, for vandal-resistant (IK10) surface-mount housing (152 mm)

Licences

004717	DLC - Casino Preset and Frame Rate 50/60 fps at 720p⁶⁾ License for the use of the Automatic Exposure (AE) preset Casino and the frame rate of 50/60 fps at 720p
---------------	--

6) The recording at 50/60 fps is supported by the DIS-2/M NSU.

DDF4520HDV-DN

Hybrid HD Dome Camera, 1.3-Megapixel, 720p/30, SD (PAL/NTSC), H.264, Day/Night (ICR), Low-Light, Wide Dynamic Range (WDR), Motor-driven Varifocal Lens, P-Iris, PoE (Class 0), Vandal-resistant (IK10)

Specifications

Sensor

Type	1/3" 1.3-megapixel CMOS image sensor
Signal processing	Pure Digital Signal Processing
Image capture	Progressive Scan
Minimum illumination	0.1 lux (F1.2, 50 IRE)
Dynamic range (WDR)	> 115 dB ⁸⁾
Signal-to-noise ratio (SNR _{MAX})	43.9 dB

Functions

Hybrid Video	On/Off
Day/Night switching	Yes, using ambient light sensing and ICR ⁷⁾ function (switching threshold level adjustable)
B/W (black-and-white) mode	Automatic ⁹⁾ (in Night mode)
Automatic Electronic Shutter (AES)	1/25(30)–1/10000 s (Auto Slow Shutter extends maximum exposure time to 1/4(5)s with AE Preset "Low light")
Digital Noise Reduction	Yes
Automatic Exposure (AE) Presets	Outdoor, Indoor, Low light, Casino ¹⁰⁾
Exposure metering mode	Average metering (light information from entire scene), centre-weighted average metering, spot metering
Brightness adjustment	Automatic (ALC)/Manual
Gain control	Automatic (AGC)
White balance	ATW (Auto Tracking White Balance), One-Push AWB (Automatic White Balance)
Privacy Zone Masking	Yes (max. 40% of the entire image)
Flip function	Horizontal, vertical or both
Digital Image Shift ¹¹⁾	Yes
Motion detection ¹²⁾ (VMD)	With selectable sensitivity (5 levels)
Alarm notification	Via DaVID Protocol (Dallmeier Video Protocol) to PGuard advance ¹²⁾ , e-mail, FTP image upload
Configuration	Via web browser
Languages	German, English, Spanish, French, Italian

Lens

Type	<i>For specifications and available angles of view see "Lens Specifications" on page 6.</i>
Zoom control (Tele–Wide)	Motor-driven (controllable via web browser)
Focus control (Far–Near)	Motor-driven (controllable via web browser)
Iris control	P-Iris (motor-driven, configurable via web browser)

Format and Encoding

Video standard	SDTV (PAL/NTSC) HDTV (SMPTE 296M)
Resolution video over IP	4CIF (PAL: 704 × 576, NTSC: 704 × 480) 720p (1280 × 720) SXGA– (1280 × 960)
Resolution analogue SD video	4CIF (PAL: 704 × 576, NTSC: 704 × 480)
Aspect ratio video over IP	4:3 (4CIF, SXGA–) 16:9 (720p)
Aspect ratio analogue SD video	Scale Analog Output -> On: 4:3 (if Encoder 1 resolution: 4CIF, SXGA–) 16:9 Letterbox (if Encoder 1 resolution: 720p)
Video compression	Scale Analog Output -> Off: 4:3 (cropped from centre sensor area) H.264, MJPEG
Frame rate	<i>See tables "Maximum Frame Rates" on page 5.</i>
Video bit rate	0.25–10 Mbit/s, CBR (constant bit rate) or VBR (variable bit rate) Video streaming Simultaneous Dual- or Tri-Streaming ¹³⁾ (<i>Note the tables "Available Encoder Combinations" on page 5.</i>)
Transfer format	Progressive (full image)
Live streaming transmission method	Unicast, Multicast

Protocols

Ethernet protocols	IPv4, TCP, UDP, ARP, ICMP, DHCP, NTP, HTTP, RTSP, IGMP V2, FTP, SMTP, RTP, RTCP
SNMP support	Yes

7) ICR = IR Cut Filter Removable

8) According to the sensor manufacturer's specifications

9) Without colour information, or rather in black-and-white mode, the image quality in low light conditions will be much clearer (e.g. less colour noise).

10) Optional license **DLC - Casino Preset and Frame Rate 50/60 fps at 720p** (004717) required. The recording at 50/60 fps is supported by the **DIS-2/M NSU**.

11) Digital Image Shift = Provides digital fine alignment of the image section (only applicable at 720p, vertical alignment by 120 pixels up or down)

12) Function in preparation

13) Only usable if analogue video output is disabled

DDF4520HDV-DN

Hybrid HD Dome Camera, 1.3-Megapixel, 720p/30, SD (PAL/NTSC), H.264, Day/Night (ICR), Low-Light, Wide Dynamic Range (WDR), Motor-driven Varifocal Lens, P-Iris, PoE (Class 0), Vandal-resistant (IK10)

Specifications (Continuation)

Connections

Video OUT	1× BNC (CVBS, 1.0V _{p-p} , 75 Ohm)
Ethernet	1× RJ45, 10BASE-T-/100BASE-TX-PoE
Power IN	12V DC (Weidmüller male connector SL 3.50/02/90G)

Miscellaneous

Ambient light sensor	Integrated
Programming interface	Open platform for integration into third-party systems using API and ActiveX*
ONVIF compliance	Core Specifications 1.01 & 1.02

Electrical Data

Voltage supply	12V DC ±10% or PoE (Class 0)
PoE standard	IEEE 802.3af
Power consumption	Max. 4.5 W

Mechanical Data

Dimensions	In-ceiling mount variant: approx. Ø 170 × H 135 mm (Ø 6.7 × H 5.3 inches) Surface mount variant: approx. Ø 152 × H 136 mm (Ø 6.0 × H 5.3 inches)
Weight	In-ceiling mount variant: approx. 1200 g (2.6 lb) Surface mount variant: approx. 1100 g (2.4 lb)
Adjustment	3-axis
Colour	White (standard variant)
Bubble	Clear (with black inner liner for discrete surveillance)
Vandal-resistant	Yes
IK protection	IK10 protection against external mechanical impacts (up to 20 joules)
IP rating	IP67 (surface mount variant only)

Environmental Conditions

Operating temperature	In-ceiling mount variant (indoor): -20°C to +40°C (-4°F to 104°F) Surface mount variant (in- and outdoor): -20°C to +50°C (-4°F to 122°F)
Relative humidity	0%–90% RH, non-condensing

Approvals/Certifications

Type	CE, FCC, ACA, UVV "Kassen" (DGUV Test), UL, DIN EN 50130-4 compliant
------	--

DDF4520HDV-DN

Hybrid HD Dome Camera, 1.3-Megapixel, 720p/30, SD (PAL/NTSC), H.264, Day/Night (ICR), Low-Light, Wide Dynamic Range (WDR), Motor-driven Varifocal Lens, P-Iris, PoE (Class 0), Vandal-resistant (IK10)

Available Encoder Combinations

Encoder 1 (H.264)

Encoder 1	Encoder 2	Encoder 3**
H.264	H.264/MJPEG	H.264
SXGA- / - 30 fps	VGA (640 × 480) / - 15 fps	-
720p / - 60 fps ¹⁴⁾	-	-
720p / - 30 fps	VGA (640 × 352) / - 30 fps	-
720p / - 30 fps	VGA (640 × 352) / - 15 fps	QCIF (192 × 128) / - 15 fps
4CIF / - 30 fps	4CIF / - 30 fps	-

Encoder 1 (MJPEG)

Encoder 1	Encoder 2	Encoder 3**
MJPEG	H.264/MJPEG	H.264
SXGA- / - 30 fps	-	-
720p / - 60 fps ¹⁴⁾	-	-
720p / - 30 fps	-	-
4CIF / - 30 fps	-	-

** only available if Encoder 2 -> MJPEG

Maximum Frame Rates

Hybrid Video Off

Resolution	Encoder 1	Analogue Output
SXGA-	25/30 fps	12.5/15 fps
720p	25/30 fps	25/30 fps
720p	50/60 fps ¹⁴⁾	- ***
4CIF	25/30 fps	25/30 fps

Hybrid Video ON

Resolution	Encoder 1	Analogue Output
SXGA-	12.5/15 fps	25/30 fps
720p	25/30 fps	25/30 fps
720p	50/60 fps ¹⁴⁾	- ***
4CIF	25/30 fps	25/30 fps

*** At 720p/50 (PAL) or 720p/60 (NTSC), no analogue video output and no encoding by Encoder 2 and Encoder 3 is possible

¹⁴⁾ Optional license **DLC - Casino Preset and Frame Rate 50/60fps at 720p** (004717) required. The recording at 50/60fps is supported by the **DIS-2/M NSU**.

All trademarks identified by © are registered trademarks of Dallmeier electronic.

All trademarks identified by * are trademarks or registered trademarks of the following owners: ActiveX of Microsoft Corporation headquartered in Redmond, Washington, USA

DDF4520HDV-DN

Hybrid HD Dome Camera, 1.3-Megapixel, 720p/30, SD (PAL/NTSC), H.264, Day/Night (ICR), Low-Light, Wide Dynamic Range (WDR), Motor-driven Varifocal Lens, P-Iris, PoE (Class 0), Vandal-resistant (IK10)

Lens Specifications

Lens F1.2 – F2.3 / 3 – 9 mm	
Type	Motor-driven megapixel varifocal lens
Format	1/2.7"
Mount	Board Lens
Focal length	3 – 9 mm
Iris range (at wide end)	F1.2 – 360 (Closed)
Iris range (at tele end)	F2.3 – 360 (Closed)
Iris control	P-Iris (motor-driven)
Zoom	Motor-driven
Focus	Motor-driven
MOD (Minimum Object Distance)	0.5 m
IR corrected	Yes
Available angles of view ¹⁵⁾ (H × V) at wide end	approx. 77° × 61° with 4CIF, SXGA– approx. 77° × 48° with 720p
Available angles of view ¹⁵⁾ (H × V) at tele end	approx. 29° × 22° with 4CIF, SXGA– approx. 29° × 17° with 720p

Lens F1.6 – F2.6 / 10 – 23 mm	
Type	Motor-driven megapixel varifocal lens
Format	1/2.7"
Mount	Board Lens
Focal length	10 – 23 mm
Iris range (at wide end)	F1.6 – F16 (Closed)
Iris range (at tele end)	F2.6 – F16 (Closed)
Iris control	P-Iris (motor-driven)
Zoom	Motor-driven
Focus	Motor-driven
MOD (Minimum Object Distance)	0.8 m
IR corrected	Yes
Available angles of view ¹⁵⁾ (H × V) at wide end	approx. 27° × 20° with 4CIF, SXGA– approx. 27° × 15° with 720p
Available angles of view ¹⁵⁾ (H × V) at tele end	approx. 11° × 8° with 4CIF, SXGA– approx. 11° × 6° with 720p

¹⁵⁾ All specifications ±5%. Minor deviations with lenses may be a result of manufacturing tolerances and do not constitute a defect.



All trademarks identified by ® are registered trademarks of Dallmeier electronic.

All trademarks identified by * are trademarks or registered trademarks of the following owners: ActiveX of Microsoft Corporation headquartered in Redmond, Washington, USA



DDF4520HDV-DN

Hybrid HD Dome Camera, 1.3-Megapixel, 720p/30, SD (PAL/NTSC), H.264, Day/Night (ICR), Low-Light, Wide Dynamic Range (WDR), Motor-driven Varifocal Lens, P-Iris, PoE (Class 0), Vandal-resistant (IK10)

Dimensions



In-ceiling mount variant



Surface mount variant