

AXIS FA51 Main Unit

Single-channel main unit with HDMI output

This modular single-channel main unit can connect to one sensor unit offering highly discreet surveillance. Featuring an HDMI output, it's possible to display live video on a public viewing monitor. And, AXIS Face Detector highlights faces within bounding boxes to let would-be shoplifters know they're being monitored and proactively reduce shoplifting. Compatible with all AXIS FA sensor units including IR sensor units, you'll enjoy excellent video quality even in complete darkness. Furthermore, Axis Edge Vault protects your Axis device ID and simplifies authorization of Axis devices on your network.

- > **HDTV 1080p at full frame rate**
- > **AXIS Face Detector preinstalled**
- > **HDMI output for public viewing monitors**
- > **1 configurable input/output port**
- > **Compatible with all AXIS FA sensor units**



AXIS FA51 Main Unit

System on chip (SoC)		Environment	IEC/EN 60529 IP4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78
Model	ARTPEC-6	Network	NIST SP500-267
Memory	1024 MB RAM, 512 MB Flash	Cybersecurity	ETSI EN 303 645
Video		Cybersecurity	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Edge security	Software: Signed firmware, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Secure boot, Axis Edge Vault with Axis device ID, signed video, secure keystore (CC EAL4+ certified hardware protection of cryptographic operations and keys)
Resolution	1920x1080 (1080p) to 160x90	Network security	IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2) ^a , IEEE 802.1AE (MACsec PSK/EAP-TLS), IEEE 802.1AR, HTTPS/HSTS ^a , TLS v1.2/v1.3 ^a , Network Time Security (NTS), X.509 Certificate PKI, host-based firewall
WDR	Forensic WDR	Documentation	<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity
Frame rate	Up to 25/30 fps in all resolutions	General	
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264 HDMI	Casing	IP4X- Aluminum casing Color: black NCS S 9000-N
HDMI output	Single camera source Playlist: single camera sources, still images 1080p 30/25/24 fps (50/60 Hz) 720p 50/60 fps (50/60 Hz) 576p 50 fps (50/60 Hz) 480p 60 fps (50/60 Hz)	Sustainability	PVC free, BFR/CFR free
Image settings	Contrast, brightness, sharpness, white balance, exposure control, exposure zones, compression, rotation: 0°, 90°, 180°, 270° including corridor format, mirroring, polygon privacy mask, control queue	Power	Power over Ethernet (PoE) IEEE 802.3af Type 1 Class 3, typical 5.2 W, max 6.82 W
Pan/Tilt/Zoom	Digital PTZ, preset positions	Connectors	RJ45 10BASE-T/100BASE-TX PoE RJ12 for sensor unit 4-pin terminal block for two configurable alarm inputs/outputs (12 V DC output, max. load 50 mA) HDMI type D
Network		Storage	Support for microSD/microSDHC/microSDXC card and encryption Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Security	IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, multi-level user, signed video, Axis Edge Vault, Axis device ID, secure keystore (CC EAL4 certified)	Operating conditions	-20 °C to 50 °C (-4 °F to 122 °F) Maximum temperature (intermittent): 60 °C (140 °F) Start-up temperature: -20 °C (-4 °F) Humidity 10–85% RH (non-condensing)
Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS ^a , TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, RTCP, DHCP, SSH, CDP, MQTT, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 10–85% RH (non-condensing)
System integration		Dimensions	24 x 49 x 152 mm (0.9 x 1.9 x 6.0 in)
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org	Weight	195 g (0.43 lb)
Event conditions	Device status, edge storage, I/O, PTZ, scheduled event, video MQTT subscribe	Included accessories	Installation guide, Windows [®] decoder 1-user license, terminal block connector
Event actions	Toggle I/O, send images, publish MQTT, send notifications, overlay text, recordings, SNMP trap messages, status LED, video clips MQTT publish	Optional accessories	AXIS T8415 Wireless Installation Tool, AXIS Surveillance Cards, AXIS T8120 Midspan 15 W 1-port For more accessories, see axis.com
Data streaming	Event data	Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms
Analytics		Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese
Applications	Included AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, AXIS Face Detector, active tampering alarm Supported AXIS People Counter, autotracking Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	Warranty	5-year warranty, see axis.com/warranty
Approvals		a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).	
EMC	EN 55035, EN 55032 Class A, EN 61000-6-1, EN 61000-6-2 Australia/New Zealand: RCM AS/NZS CISPR 32 Class A Canada: ICES-3(A)/NMB-3(A) Japan: VCCI Class A Korea: KC KN32 Class A, KC KN35 USA: FCC Part 15 Subpart B Class A		
Safety	IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, IS 13252		