

DS-2CE16C0T-IRF 1 MP Fixed Mini Bullet Camera



- HD 720p bullet camera
- Smart IR: up to 20 m IR distance
- Water and dust resistant (IP67)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

▪ Specification

Camera	
Image Sensor	1 MP CMOS image sensor
Max. Resolution	1280 (H) × 720 (V)
Min. Illumination	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s;NTSC: 1/30 s to 1/50,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 180°, Rotation: 0° to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm, 6 mm optional
Focal Length & FOV	Field of view: 70.9° (3.6 mm), 92° (2.8 mm), 56.7° (6 mm)
Lens Mount	M12
Illuminator	
Supplement Light Type	IR
Supplement Light Range	Up to 20 m
Smart Supplement Light	Yes
Image	
Frame Rate	720p@25fps/720p@30fps
SNR	>62 dB
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS,1 HD analog output
General	
Power	12 V DC±15%, max. 4 W
Dimension	Φ 70 mm × 154.5 mm (2.76" × 6.08")
Weight	400 g (0.88 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation)
Approval	
Protection	IP67

▪ Available Model

DS-2CE16COT-IRF(2.8mm)

DS-2CE16COT-IRF(3.6mm)

DS-2CE16COT-IRF(6mm)

- **Accessory**
- **Optional**

**DS-1280ZJ-XS
Junction Box**



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

