



SPA-B1000

IP Audio Bridge



Key Features

- Maximum Input Level: L, R : +6dBV Max
- Power: PoE (IEEE 802.3 af type 1 Class 0), DC 24V
- Internal Memory: 1 GBytes
- External Memory (Micro SD): SDHC upto 32GB (SANDISK)
- Supported Protocol: IPv4, HTTP, HTTPS, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP
- Supported Supported Audio Format: WAV, MP3 in mono/stereo from 64 kbps to 320 kbps (File Streaming). Sampling rate from 16 kHz up to 48 kHz

SPA-B1000

IP Audio Bridge



Specifications

Product	
Type	IP Audio Bridge
Line Input	
Maximum Input Level	L, R : +6dBV Max
Network	
Ethernet	10/100 Base-T
Memory	
Internal Memory	1 GBytes
External Memory (Micro SD)	SDHC upto 32GB (SANDISK)
Contact	
Contact Input. Dry contact	One channel
Contact Output. Dry contact (NO)	One channel
General	
Operating Temperature	-20 ~ +50°C (-4°F ~ +122°F)
Operating Humidity	10~95% RH (Non-Condensing)
Weight	0.24 Kg
Size	123(W)*80(H)*30.6(D)mm
Color	White
Certificate	EMC : KS C 9832/9835, EN 55032/55035, FCC Part 15 Subpart B, ICES-003 Safety : KC 62368-1, UL 62368-1, CAN/CSA 62368-1
Power	
PoE	PoE (IEEE 802.3 af type 1 Class 0), DC 24V
Audio	
Supported Audio Format	File Streaming: WAV, MP3 in mono/stereo from 64 kbps to 320 kbps. Sampling rate from 16 kHz up to 48 kHz
Network Protocol	
Security	Password protection : admin,setup,user,guest (sha-2, Digest authentication, User access log) Digest authentication, User access log
Supported Protocols	IPv4, HTTP, HTTPS, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP
System Integration	

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com.

Hanwha Vision is formerly known as Hanwha Techwin.

API (Application Programming Interface)	SUNAPI
Event & Preset	Virtual Contact, Dry contact
Functional Monitoring	Connection verification, Built-in system logging

SPA-B1000

IP Audio Bridge



CAD

Unit:mm [inch]

