

DS-D4239TI-SLC Transparent LED Display



The full-color transparent LED display standard series, featuring with high brightness, high contrast, and ultra-wide viewing angle, can achieve quality display effects from different viewing angles. Designed with light and thin structure, the transparent LED display is small in size and cost-effective in maintenance, which is widely applicable to glass curtain wall, glass shopcase, commercial complex, space design, etc.

- Standardized cabinet for flexible installation, multi-screen seamless splicing with light and thin design, and convenient for quick installation.
- Permeability-oriented material selection and design, no influence on the original building appearance.
- Brightness customizable on the basis of specific scenarios, ensuring the display effects even under the highlight indoor or the direct sunlight outdoor.
- Runs silently with lower heat and effective heat dissipation.



▪ Specification

Model		DS-D4239TI-SLC
Cabinet	Pixel Configuration	1R1G1B
	Pixel Pitch	Horizontal: 3.9 mm, Vertical: 7.8 mm
	Dimensions (W × H × D)	Different dimensions for flexible splicing: 1 m × 1 m, 1 m × 0.75 m, 0.75 m × 1 m, 0.75 m × 0.75 m, 1 m × 1.25 m, 1.25 m × 1 m
	Weight	15 kg/m ²
	Pixel Density	32768 dot/m ²
	Cabinet Material	Aluminum alloy
	Protection Level	IP43
Display	White Balance Brightness	5500 nit (highlight)
	Color Temperature	2000K to 10000K adjustable
	Viewing Angle	120° (H)/120° (V)
	Brightness Uniformity	≥ 98%
	Color Uniformity	± 0.001 Cx, Cy
	Contrast Ratio	≥ 3000:1
	Transmittance	60%
	Display Color	281.4 trillion
Processing Performance	Brightness Control	Manual/Auto
	Driving Method	Constant current driving 1/4 scan
	Frame Frequency	60 Hz
	Refresh Rate	≥ 1920 Hz
	Grey Level	65536 Level
	Processing Depth	16 bits
Power	Max. Consumption	800 W/m ²
	Average Consumption	300 W/m ²
	Input Voltage	110 to 220 VAC ± 15%
Working Environment	Working Temperature	-10 °C to 65 °C (14 °F to 149 °F)
	Working Humidity	10% to 90%
	Storage Temperature	-20 °C to 90 °C (-4 °F to 194 °F)
	Storage Humidity	10% to 90%

Available Model

DS-D4239TI-SLC

Distributed by

**HIKVISION****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 [216]521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com