

**DS-D42A0FO-CLF/C**  
**P10 Outdoor Fixel LED Display Unit**



- Support rear maintenance
- Using aluminum chassis, good heat dissipation and can work under 60 °C
- All series aluminum profile cabinets support front and rear IP66
- Apply unique technology, maximally saving 50% energy
- Various cabinet sizes, applying to diverse scenes
- The cabinets support customized 45° corner cut to realize 90° right-angle splicing

## ▪ Specification

Model		DS-D42A0FO-CLF/C
Cabinet	Pixel Configuration	1R1G1B
	Pixel Pitch Category	P10
	Pixel Pitch	10 mm
	Modules Component	Aluminum Shell
	Dimensions (W × H × D)	120 mm × 960 mm × 127 mm (4.73" × 37.8" × 5.00")
	Resolution	12 × 96
	Area	0.1152
	Weight	5 KG/PCS
	Pixel Density	1152/cabinet
	Lamp Board Housing	YES
	Cabinet Material	Aluminum Profile
	Maintenance Method	Back Maintenance
	Cabinet Flatness	0.8 mm
	Protection Level	IP67(F)/IP66(R)
Display	White Balance Brightness	6000
	Color Temperature	3000 K to 10000 K
	Viewing Angle	160° (H)/80° (V)
	Contrast Ratio	8000:1
	Color Uniformity	≥ 0.95
	Brightness Uniformity	≥ 0.95
Processing Performance	Driving Method	Constant Current
	Frame Frequency	50/60 HZ
	Refresh Rate	3840
	Grey Level	14 bit
	Display Color	DCI-P3 > 85%
Power	Power Supply	110 to 220
	Max. Consumption	580
	Average Consumption	200
Working Environment	Working Temperature	-40 to 60 °C
	Working Humidity	10% to 95% RH (non-condensing)
	Storage Humidity	10% to 95% RH (non-condensing)
	Storage Temperature	-40 to 80 °C
General	Gross Weight	10
	Package Dimensions (W × H × D)	1040 mm × 160 mm × 200 mm
	Lifespan	100000 Hours

## ▪ Available Model

DS-D42A0FO-CLF/C

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
[www.hikvision.com](http://www.hikvision.com)



Follow us on social media to get the latest product and solution information.

