SPCK520/SPCK521 Compact Keypad

Touch keypad with graphical display, card reader and audio annunciation

- Stylish and slim (depth of 17.5mm)
- Touch key technology
- Fade in / fade out key interface provides a smooth, uniform appearance when not in use
- Integrated card readers: EM and Mifare card technologies supported
- Audio support: The built in speaker supports audio features such as voice annunciation.
- Additional plugin wireless option (SPCW114)
- Flush mount option also available
- Large graphical interface provides user friendly operation in single area and multi-area installations
- Push wire terminals allow quicker for installation
- Backward compatible with existing SPC systems (V3.4.5 and later)

Answers for infrastructure.

SIEMENS

■ Technical data

Display	128 x 64 pixels (approx. 6 x 20 characters)
LED indicators	5 status LEDs
Special keys	4 soft keys, 4 menu navigation keys
Interfaces	X-BUS (in, out)
Operating voltage	9.5 ~ 14 V DC
Tamper contact	On-board front/back tamper switch
Operating temperature	5° ~ +40 °C
Housing	Plastic housing (PMMA, PC ABS, ABS)
Colour	RAL 9003 (signal white)
Dimensions	110 x 150 x 17.5 mm
Weight	0.250 kg
Operating current	**SPCK520** - Max. 210 mA at 12 V DC (backlight, LEDs and voice annunciation operated) **SPCK521** - Max. 210 mA at 12 V DC (backlight, LEDs and voice annunciation operated)
Quiescent current	**SPCK520** - Max. 55 mA at 12 V DC **SPCK521** - Max. 95 mA at 12 V DC
Supported card technologies	**SPCK521** – EM 4102 and Mifare
Audio	Supported via integrated speaker

■ Details for ordering

Type	Ordering No:	Description	Weight*
SPCK520.100-N	S54543-F115-A100	Compact Keypad Neu.	0.325 Kg
SPCK521.100-N	S54543-F116-A100	Compact Keypad w. CR Neu.	0.325 Kg

* Unit incl. Packing material, accessories that are included in the delivery, and documentation

Further products and accessories can be found in the Internet: siemens.com/securityproducts