DS-KIS101-P/Flush Video Intercom Two-Wire Analog Bundle







Key Feature

- 2-Wire plug & play, easy, cost-efficient
- Receive video call and Unlock via indoor station
- 7-inch TFT screen with 1024*600 resolution
- 2MP HD colorful camera
- View in color, even in darkness
- One-touch calling with nametag
- IP65 water resistant, preventing from water ingress
- IK7 vandal resistant
- 2 lock relays, power supply for one electric lock (Up to 12V 1A)

Specification

Door station	
Supplement light	White light supplement
Lens	Low Illumination 2 MP HD IR Camera
FOV	Horizontal: 100°, Vertical: 69°
WDR	Support
Resolution	2MP
Door station	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker (More than 80 dB within 20 cm)
Volume	Adjustment with screwdriver
adjustment	
Door station	
Alarm input	4
Two-Wire	1
TAMPER	1

Exit button	2
Lock control	2, locking time can be adjusted via DIP
	switch (Max. 7 s)
Door contact	2
input	2
Power supply	1, Max. 12 V 1 A
for lock	
Debugging port	1
Door station	
Button	1
Installation	Flush mounting
Protective level	IP65, IK7
Working	-30 ° C to +60 ° C (-22 ° F to 140 ° F)
temperature	30 610 100 6 (22 1 10 140 1)
Working	10% to 90%
humidity	10/8 to 30/8
Dimensions	150 mm \times 82 mm \times 23.5 mm (5.91" \times 3.23" \times 0.93")
Power supply	48 VDC, 0.5 A
Application	Outdoor
environment	Outdoor
Power	≤ 12 W
consumption	
Door station	
Operation	Embadded analog eneration system
system	Embedded analog operation system
Indoor station	
Size	7-inch TFT non-touch screen
Operation	6 touch buttons
method	
Туре	Colorful TFT screen



Resolution	1024 × 600
Indoor station	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker (More than 80 dB within 20 cm)
Audio quality	/
Volume	Adjustable with touch-button
Audio	
compression	/
Rate	
Indoor station	
Two-wire	3
Indoor station	
Power supply	48 VDC
Power	≤ 5 W
consumption	
Working	-10 ° C to 50 ° C (14 ° F to 122 ° F)
temperature	-10 C to 30 C (14 F to 122 F)
Working	10% to 90%
humidity	
Dimensions (W	187 mm $ imes$ 137 mm $ imes$ 25.4 mm (7.36"
imes H $ imes$ D)	× 5.39" × 1.00")
Installation	Surface mounting
Button	6
Indoor station	
Operation	Embedded analog operation system
system	

5 :	
Dimension	١

No.

1

2

3

4

5

6

7

8

9

10

11

Description

Screen

Microphone

Volume +

Volume -

Receive

/Decline

Unlock Door

2

Unlock Door

1

Monitor

/Switch

Terminals

Loudspeaker

Power

Terminal

No.

12

13

14

15

16

17

18

19

20

21

22

Description

DIP Switch

Debugging Port

Camera

Loudspeaker

Call Button

Microphone

TAMPER


Terminals

Debugging Port

DIP Switch


Volume

Adjust





Unit:mm




Unit:mm

Available Model

DS-KIS101-P/Flush

Physical Interface





Distributed by



Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T+86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T +1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T+31-23-5542770 sales,eu@hikvision.com

Hikvision Italy T+39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T+90 [216]521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales,my@hikvision.com Hikvision UK & Ireland T+01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 [10] 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T+82-[0]31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com

Dikivision Digital Technology Co., Ltd. 2020 | Data subject to change without notice |