

## DS-K1107AEK Card Reader



- Equipped with the 32-bit high-speed processor
- RS-485 and Wiegand (W26/W34) protocol, and OSDP protocol
- Build-in EM card reading module (Frequency:125KHz).
- Supports tampering alarm
- Built-in buzzer for identifying the reading status
- Online upgrade function
- Watchdog design for repairing itself in case that exception occurs, to ensure the long service life of the reader

## ▪ Specification

Interface	
TAMPER	1
RS-485	1
Wiegand	1 (set via DIP switch)
Authentication	
Card reading frequency	125 KHz
General	
Power supply	12 VDC
Power consumption	≤ 2 W
Working temperature	-20 °C to 65 °C (-4 °F to 149 °F)
Working humidity	10% to 90% (no condensing)
Dimensions	115 mm × 44 mm × 22 mm (4.53" × 1.73" × 0.87")
Installation	Wall mounting with screws; Do not support gang box
Weight	Gross weight: 0.25 kg (0.55 lb) Net weight: 0.14 kg (0.31 lb)
Keypad	12 keys (0 to 9, *, #)
Buzzer	Support

## ▪ Available Model

DS-K1107AEK

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

