

DS-K1T502DBWX Access Control Terminal



- Manage access control, intercoms, and security with one device
- IP65 & IK09 protections, as well as increased stability with zinc alloy materials
- Multiple authentication methods, including card, etc.
- Remote control via the Hik-Connect mobile app
- Connects to external access controller via Wiegand protocol
- Two-way audio via SIP 2.0 protocol
- RS-485 communication for connecting external card reader


▪ Specification

System	
Operating system	Linux
Network	
Wired network	10 M/100 M self-adaptive
Wi-Fi	Support
Bluetooth	Support
Interface	
Network interface	1
Lock control	1
Exit button	1
Door contact input	1
Alarm input	1
Alarm output	1
TAMPER	1
RS-485	1
Wiegand	1 (Output only)
SD Card Slot	1
Capacity	
Card capacity	100,000
Event capacity	300,000
Authentication	
Card type	Mifare 1 card, DESfire card
Card reading distance	0 ~ 3 cm
Function	
Two-way audio	Support
Hik-Connect	Support
General	
Power supply	1 A (DC 12 V ~ DC 24 V)
Power consumption	≤12 W
Working temperature	-40 °C ~ +70 °C (-40 °F ~ +158 °F)
Protective level	IK09, IP65
Language	Arabic, English, French, Indonesian, Italian, Portuguese (Brazil), Russian, Spanish (Europe), Thai, Ukrainian, Vietnamese


▪ Available Model

DS-K1T502DBWX

▪ Dimension



2 mm 24.1 mm



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

