

## DS-KD8003-IME1(B)/NS KD8 Series Pro Modular Door Station



- Main unit of modular door station
- 2 MP fisheye camera with IR supplement
- Two-lock control
- Standard PoE power supply
- IP65 protection level
- Convenient configuration via Web remotely
- Directly provide 12 V, 500 mA power output for one electronic lock without additional power supply
- Stainless Steel high quality material

## ▪ Specification


System parameters	
Operation system	Linux
ROM	32 MB
RAM	256 MB
Processor	Embedded high performance processor
Display parameters	
Screen size	/
Operation method	/
Type	/
Resolution	/
Video parameters	
Lens	2 MP HD camera
Resolution	2 MP
FOV	Horizontal: 146°, Vertical: 82°
Wide dynamic range (WDR)	Support
Supplement light	Low illumination, IR supplement lights
Video compression standard	H.264
Audio parameters	
Audio input	1 built-in omnidirectional microphone
Audio compression standard	G.711 U/G.711 A
Audio output	1 built-in loudspeaker
Audio compression bitrate	64 Kbps
Audio quality	Noise suppression and echo cancellation
Volume adjustment	Adjustable
Capacity	
User capacity	2000
Face capacity	/
Fingerprint capacity	/
Card capacity	6000
Message capacity	/
Linked indoor station capacity	500
Sub door station capacity	16
Network parameters	
Network protocol	TCP/IP, RTSP
Wi-Fi	/
Bluetooth	/
3G/4G	/
Device interfaces	
Alarm input	4 (2 exit buttons and 2 door contacts by default)
Network interface	1 RJ-45, 10/100 Mbps self-adaptive
TAMPER	1
Exit button	2 (2 for lock control)
RS-485	1 (1 for Hikvision's sub module communication)
USB	/
Wiegand	/

TF card	/
Alarm output	/
Lock control	2 relays, Max. 30 VDC, 2 A
Door contact input	1
Two-Wire IP interface	/
<b>General</b>	
Button	/
Installation	Surface mounting, flush mounting
Indicator	/
Weight	Net weight: 410 g Gross weight: 581 g
Protective level	IP65
Working temperature	-40 °C to 60 °C (-40 °F to 140 °F)
Working humidity	10% to 95% (no-condensing)
Dimension (W × H × D)	98 mm × 100 mm × 42 mm (3.86" × 3.94" × 1.65")
Battery	/
Power supply	12 VDC, 500 mA, IEEE 802.3af, PoE
Application environment	Outdoor
Power consumption	≤ 5 W
Language	English, French, Portuguese, Brazilian Portuguese, Spanish, Russian, German, Italian, Polish, Turkish, Vietnamese, Arabic, Czech, Hungarian, Dutch, Romanian, Bulgarian, Ukrainian, Croatian, Serbian, Greek, Slovak

### ▪ Available Model

DS-KD8003-IME1(B)/NS

### ▪ Dimension



▪ **Accessory**

▪ **Optional**

<b>DS-KAW50-1</b>	<b>DS-KD-IN</b> KD8 Series Pro Modular Door Station	<b>DS-KD-BK</b> KD8 Series Pro Modular Door Station	<b>DS-KD-M</b> KD8 Series Pro Modular Door Station	<b>DS-KD-E</b> KD8 Series Pro Modular Door Station
				
<b>DS-KD-DIS</b> KD8 Series Pro Modular Door Station	<b>DS-KD-INFO</b> KD8 Series Pro Modular Door Station	<b>DS-KABD8003-RS1</b> Rain Shield of Module Door Station	<b>DS-KABD8003-RS2</b> Rain Shield of Module Door Station	<b>DS-KABD8003-RS3</b> Rain Shield of Module Door Station
				
<b>DS-KAW50-1N</b>	<b>DS-KD-ACF1/S</b> 2nd Video Intercom Brackets	<b>DS-KD-ACF2/S</b> 2nd Video Intercom Brackets	<b>DS-KD-ACF3/S</b> 2nd Video Intercom Brackets	<b>DS-KD-ACW1/S</b> 2nd Video Intercom Brackets
				
<b>DS-KD-ACW2/S</b> 2nd Video Intercom Brackets	<b>DS-KD-ACW3/S</b> 2nd Video Intercom Brackets	<b>DS-KD-KK/S</b> KD8 Series Pro Modular Door Station	<b>DS-KD-KP/S</b> KD8 Series Pro Modular Door Station	<b>DS-KD-TDM</b>
				

				
<b>DS-KD-TDE</b>	<b>DS-KABD8003- RS1/S</b>	<b>DS-KABD8003- RS2/S</b>	<b>DS-KABD8003- RS3/S</b>	
				

**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

