

U/UTP 4Pairs cable-category5E-PVC Sheath

P/N: HK-1191-C5E-003-01

Content of the Data Sheet

HIKVISION E484059-Z CMX (UL) 4PR 24AWG 75 °C U/UTP CAT5E VERIFIED TO		ANSI/TIA-568-C.2 PVC ****m mm/dd/yyyy																																																													
Customer Reference																																																															
Category	U/UTP CAT5E-4P- PVC-CMX																																																														
Test Standard	ISO/IEC11801、TIA-568-C.2 YD/T1019																																																														
Conductor	Material	Solid-Bare Copper																																																													
	Copper content	99.97%																																																													
	Nom.O.D.(mm)	up	+0.005																																																												
down		-0.005																																																													
Insulation	Material	HDPE																																																													
	Diameter	0.82±0.03mm																																																													
Sheath	Thickness	0.50±0.05 mm		Technical Performance(100m): <table border="1"> <thead> <tr> <th rowspan="2">Frequency (MHz)</th> <th>RL</th> <th>ATT</th> <th>NEXT</th> <th>Phase DELAY</th> </tr> <tr> <th>≥dB</th> <th>≤dB</th> <th>≥dB</th> <th>≤ns</th> </tr> </thead> <tbody> <tr><td>1</td><td>19.0</td><td>3.0</td><td>60.0</td><td>521</td></tr> <tr><td>4.0</td><td>19.0</td><td>3.9</td><td>54.8</td><td>504</td></tr> <tr><td>8.0</td><td>19.0</td><td>5.5</td><td>50.0</td><td>500</td></tr> <tr><td>10.0</td><td>19.0</td><td>6.2</td><td>48.5</td><td>498</td></tr> <tr><td>16.0</td><td>19.0</td><td>7.9</td><td>45.2</td><td>496</td></tr> <tr><td>20.0</td><td>19.0</td><td>8.9</td><td>43.7</td><td>495</td></tr> <tr><td>25.0</td><td>18.0</td><td>10.0</td><td>42.1</td><td>495</td></tr> <tr><td>31.25</td><td>17.1</td><td>11.2</td><td>40.5</td><td>494</td></tr> <tr><td>62.5</td><td>14.1</td><td>16.2</td><td>35.7</td><td>492</td></tr> <tr><td>100</td><td>12.0</td><td>21.0</td><td>32.3</td><td>491</td></tr> </tbody> </table>	Frequency (MHz)	RL	ATT	NEXT	Phase DELAY	≥dB	≤dB	≥dB	≤ns	1	19.0	3.0	60.0	521	4.0	19.0	3.9	54.8	504	8.0	19.0	5.5	50.0	500	10.0	19.0	6.2	48.5	498	16.0	19.0	7.9	45.2	496	20.0	19.0	8.9	43.7	495	25.0	18.0	10.0	42.1	495	31.25	17.1	11.2	40.5	494	62.5	14.1	16.2	35.7	492	100	12.0	21.0	32.3	491
	Frequency (MHz)	RL	ATT			NEXT	Phase DELAY																																																								
		≥dB	≤dB		≥dB	≤ns																																																									
	1	19.0	3.0		60.0	521																																																									
	4.0	19.0	3.9		54.8	504																																																									
8.0	19.0	5.5	50.0		500																																																										
10.0	19.0	6.2	48.5		498																																																										
16.0	19.0	7.9	45.2		496																																																										
20.0	19.0	8.9	43.7		495																																																										
25.0	18.0	10.0	42.1		495																																																										
31.25	17.1	11.2	40.5	494																																																											
62.5	14.1	16.2	35.7	492																																																											
100	12.0	21.0	32.3	491																																																											
External O.D.	4.7±0.4 mm																																																														
Surface	Clean,Frap,Satiation																																																														
Material	PVC(complies RoHS),CM																																																														
Color	Grey ZLC1003																																																														
Surface Printing	Letter height	3.0±0.3mm																																																													
	Color	Black																																																													
	Print error & Space	≤±0.5%, 1m																																																													
Core Color	1 White- Blue /Blue	2 White-Orange /Orange																																																													
	3 White- Green /Green	4 White- Brown /Brown																																																													
Packing	Wooden Tray & Carton		<table border="1"> <thead> <tr> <th rowspan="2">Frequency (MHz)</th> <th>PSNEXT</th> <th>ELFEXT</th> <th>PSELFEXT</th> </tr> <tr> <th>≥dB</th> <th>≥dB</th> <th>≥dB</th> </tr> </thead> <tbody> <tr><td>1</td><td>57.0</td><td>58.6</td><td>55.6</td></tr> <tr><td>4</td><td>51.8</td><td>46.6</td><td>43.6</td></tr> <tr><td>8</td><td>47.0</td><td>40.6</td><td>37.5</td></tr> <tr><td>10</td><td>45.5</td><td>38.6</td><td>35.6</td></tr> <tr><td>16</td><td>42.2</td><td>34.5</td><td>31.5</td></tr> <tr><td>20</td><td>40.7</td><td>32.6</td><td>29.6</td></tr> <tr><td>25</td><td>39.1</td><td>30.7</td><td>27.7</td></tr> <tr><td>31.25</td><td>37.5</td><td>28.7</td><td>25.7</td></tr> <tr><td>62.5</td><td>32.7</td><td>22.7</td><td>19.7</td></tr> <tr><td>100</td><td>29.3</td><td>18.6</td><td>15.6</td></tr> </tbody> </table>	Frequency (MHz)	PSNEXT	ELFEXT	PSELFEXT	≥dB	≥dB	≥dB	1	57.0	58.6	55.6	4	51.8	46.6	43.6	8	47.0	40.6	37.5	10	45.5	38.6	35.6	16	42.2	34.5	31.5	20	40.7	32.6	29.6	25	39.1	30.7	27.7	31.25	37.5	28.7	25.7	62.5	32.7	22.7	19.7	100	29.3	18.6	15.6													
Frequency (MHz)	PSNEXT	ELFEXT	PSELFEXT																																																												
	≥dB	≥dB	≥dB																																																												
1	57.0	58.6	55.6																																																												
4	51.8	46.6	43.6																																																												
8	47.0	40.6	37.5																																																												
10	45.5	38.6	35.6																																																												
16	42.2	34.5	31.5																																																												
20	40.7	32.6	29.6																																																												
25	39.1	30.7	27.7																																																												
31.25	37.5	28.7	25.7																																																												
62.5	32.7	22.7	19.7																																																												
100	29.3	18.6	15.6																																																												
Carton dimension	Per request																																																														
Packing length	305±1.5m/80±0.5m																																																														
Rip-cord	Yes	Drain wire	No																																																												
	<table border="1"> <thead> <tr> <th rowspan="2">Before Aging</th> <th>Tensile Strength (Mpa)</th> <th>≥13.5</th> </tr> <tr> <th>Elongation(%)</th> <th>≥150</th> </tr> </thead> <tbody> <tr><td colspan="3">Aging Period(°C×hrs) 100°C×24h×10d</td></tr> <tr> <th>After Aging</th> <th>Tensile Strength(Mpa)</th> <th>≥12.5</th> </tr> <tr> <th></th> <th>Elongation(%)</th> <th>≥125</th> </tr> <tr><td colspan="3">Cold bend(-20±2°C×4h) 8×Cable O.D., No visible cracks</td></tr> </tbody> </table>			Before Aging	Tensile Strength (Mpa)	≥13.5	Elongation(%)	≥150	Aging Period(°C×hrs) 100°C×24h×10d			After Aging	Tensile Strength(Mpa)	≥12.5		Elongation(%)	≥125	Cold bend(-20±2°C×4h) 8×Cable O.D., No visible cracks																																													
Before Aging	Tensile Strength (Mpa)	≥13.5																																																													
	Elongation(%)	≥150																																																													
Aging Period(°C×hrs) 100°C×24h×10d																																																															
After Aging	Tensile Strength(Mpa)	≥12.5																																																													
	Elongation(%)	≥125																																																													
Cold bend(-20±2°C×4h) 8×Cable O.D., No visible cracks																																																															
Sheath Physical Properties																																																															
Electrical Characteristics (20°C)	1.0-100.0MHz Impedance(Ω)	100±15																																																													
	1.0-100.0MHz Delay Shew (ns/100m)	≤45																																																													
	DC ResistanceΩ/100m) max	14.8																																																													
	DC Conductor Resistance Unbalance(%) max	5.0																																																													
Ambient temperature: -20°C - 70°C																																																															