

ENTRY-LEVEL POWER DISTRIBUTION WITH LED PANEL

Provides reliable power distribution with real-time load monitoring for connected equipment

Ideal for server room and data center applications, the Metered PDU Series is a power distribution device that delivers electricity from a single source to multiple devices. The PDUs' built-in LED panel can clearly show the real-time load monitoring in amps. The products also feature overload protection, external site ground pin, industrial-grade metal housing, adjustable mounting brackets, long input power cord, and cord retention tray.

APPLICATION


- Office
- Server room
- Factory
- Surveillance systems
- Networking devices
- Satellite devices
- Workstations
- Back office
- Data center
- Security systems
- Telecom devices
- NAS/Storage devices
- Multimedia devices

SERIES FEATURES

- Real-Time Local Monitoring
- Cord Retention Tray
- Industrial-grade Metal Housing
- Adjustable Mounting Brackets

PRODUCT CALLOUTS

1. AC Inlet
2. Output Circuit Breaker
3. Ground Stud
4. AC Outlets
5. Meter Readout
6. Cord Retention Tray Screw Holes



TECHNICAL SPECIFICATIONS

Model Name	PDU20MVHVIEC24F
Input	
Nominal Input Voltage (Vac)	200 - 240
Input Frequency (Hz)	50 / 60
Maximum Input Current (A)	16
Input Connector Type	IEC C20 x 1
Power Cord Length (m.)	3.05
Output	
Over Current Protection (Each Bank) (A)	16
Outlets - # of Bank(s) (Bank)	1
Outlet(s) - Total	24
Outlet(s) - Front	24
Outlet Type	IEC C13 x 20, IEC C19 x 4
Management & Communications	
LED Indicators	Load
Physical	
Installed Rack Height (U)	0
Cord Retention Tray	Yes
Physical Size	
Dimensions (WxHxD) (mm.)	44.45 x 1219.2 x 38.1
Weight (kg.)	2.63
Environmental	
Operating Temperature (°C)	0 - 35
Operating Relative Humidity (Non-condensing) (%)	0 - 95
Certifications	
Certifications	CE, UL60950
RoHS	Yes

#All specifications are subject to change without notice.

